



Zoom Camera

ATC-HZ7809W-LTA


- 1/2" EXMOR R Progressive Scan CMOS
- 108x AF Zoom(9x optical zoom, 12x digital zoom)
- 1080p 60(50fps)
- Mechanical Day&Night
- True WDR
- 3D DNR, Defog
- UART RS232-TTL(Pleco-D, Pelco C, VISCA, Hitachi)



Zoom Camera

ATC-HZ7809W-LTA

Dimensions



Specifications

Image Sensor	1/2" EXMOR R Progressive Scan CMOS	
Effective Pixels	2.13MP 1945(H) x 1097(V)	
Video Output mode	HD-SDI/EX-SDI(V1.0)/CVBS TVI/AVI/LVDS	
Max. Video Resolution	HD-SDI/LVDS:1080p@60(50fps), EX-SDI/TVI/AVI:1080p@30(25fps)	
Synchronization system	Internal	
Min.Illumination	Day mode: 0.1(Lux(F1.5)) Night mode: 0.05Lux(F1.5/ IR-cut filter on) Sens-Up off, AGC28dB	
S/N Rate	More than 52dB(AGC off, Sens-Up off)	
Lens	Type	AF Optical zoom lens(DC Iris), IR Corrective
	Focal Length	f=8.0mm~70mm
	F-value	F1.5(W)~2.1(T)
	Angle of View	Horizontal 50.8°(W)~5.7°(T), Vertical 28.8°(W)~3.2°(T)
Zoom ratio	Optical 9x / Digital 12x	
Focus Min.Working Distance	0.1m(Wide)/0.5m(Tele)~∞	
Focus Control	Auto/Manual/Interval/One Shot/Preset	
AE mode	Auto/Shutter Priority/Iris Priority/Manual	
Brightness	0~14	
Manual Shutter	1/1, 1/2, 1/4(3), 1/8(6), 1/15(12),1/30(25), 1/60(50)~1/30000	
Manual Iris	F1.6~F19, Close	
Sense-up	Off~32fields	
ETC	Spot AE, Slow AE	
D&N Mode	Auto/Day(Color)/Night(BW)/External-H or L	
White Balance	AUTO/ATW/Indoor/Outdoor/OnePush/Manual	
Image Freeze	Off/On	
Image Flip	Off/Horizontal/Vertical/H+V(180° Flip)	
Privacy Mask Zone	16 Zones/14 mask color selectable, semi-transparency	
Digital Image Stabilization	Yes	
Motion Detection	4 Zones	

D-WDR	Off/Low/Middle/High	
WDR	Off/Low/Middle/High	
BLC	Off/On, Area selectable	
HLC	Off/0~20, Color selectable	
AGC	Max.58dB	
Sharpness	Adjustable(0~15)	
3D-DNR	On/Off(1~5)	
2D-DNR	Auto/Manual	
Defog	Off/Low/Middle/High	
Preset Position	256 position Presets(Zoom,Focus), 16Memory Presets, Custom Preset	
Language	English,Janpanese,Russian,Spanish, German,France,Portuguese	
UART	Remote	RS232 TTL +5.0V(+3.3V compatible)
	Protocol	VISCA/Pelco-D/Pelco-P/Hitachi: Automatic detection
	Baud rate	2400/4800/9600/19200/38400/57600/115200bps
UTC	TVI/AVI-UTC	
Supply Voltage	12VDC(9V to 15VDC)	
Power Consumption	Max.5.5W / Non-working zoom&focus 3.3W	
Dimension(mm)	50.3X58.4X92.0mm	
Weight	Approx.260.5g	
Operating Temperature	-10°C~+50°C, Humidity(20~80%)	
Storage Temperature	-20°C~+60°C, Humidity(20~95%)	